

LEVEL BAND

DAMP-PROOF COURSE FOR FOUNDATIONS



WATERPROOF

It effectively blocks humidity due to capillary action, while offering excellent resistance to water, air and wind.

VERSATILE

Available in three versions: ideal both as a wall barrier and to seal vertical wall - wall joints.



TECHNICAL DATA




Properties	standard	value	USC units
Tensile strength MD/CD	EN 12311-2	$\geq 20/\geq 20$ N/mm ²	$\geq 2.9/\geq 2.9$ lbf/mil ²
Elongation MD/CD	EN 12311-2	$\geq 550/\geq 600$ %	-
Resistance to nail tearing MD/CD	EN 12310-1	$\geq 120/\geq 120$ N/mm ²	$\geq 17.4/\geq 17.4$ lbf/mil ²
Impact resistance	EN 12691	> 500 mm	-
Watertightness after artificial ageing	EN 1296 - EN 1931	compliant	-
Watertightness	EN 1928	compliant	-
Alkaline water vapour resistance	EN 1847 - EN 1931	compliant	-
Flexibility at low temperatures	EN 495-5	-30 °C	-22 °F
Resistance to temperature	-	-40/+90 °C	-40/+194 °F
Storage temperature ⁽¹⁾	-	+10/+25 °C	+50/+77 °F

⁽¹⁾Store the product in a dry, covered location.

Waste classification (2014/955/EU): 17 02 03.

CODES AND DIMENSIONS

CODE	B [mm]	s [mm]	L [m]	B [in]	s [mil]	L [ft]	
1 LEVEL085	85	0,17	25	3.4	7	82	2
2 LEVEL125	125	0,17	25	4.9	7	82	2
3 LEVEL350	350	0,17	25	13.8	7	82	2



ADAPTABLE

The soft and elastic polyethylene profile allows it to be installed even in complex shapes and angles.

COST-PERFORMANCE

The choice of materials and optimisation in production results in a solution that offers a good balance between performance and cost.