D 38 RLE

4-SPEED DRILL DRIVER

HIGH PERFORMANCE

Powerful and resistant 2000 W motor, able to reach a tightening torque of > 250 Nm at 1st speed.

Continuously variable speed adjustment in every gear.

MAINTENANCE-FREE

4-Speed transmission with continuous lubrication.

Convenient positioning of right/left rotation switching and speed regulator.





CODES AND DIMENSIONS

CODE	description		pcs
DUD38RLE	4-Speed drill driver		1
RENTD38SET	rental machine for USA (includes DUD38RLE, DUD38SH and DUVSK)		1

Scope of supply: 4-speed machine D 38 RLE, removal wedge in cardboard box. Use of the machine only with the safety clutch (DUVSKU) and the second grip (DUD38SH) is strongly recommended.

COMPLEMENTARY PRODUCTS

CODE	description	pcs
DUVSKU	VSKU clutch	1
DUD38SH	screw handle D38SH	1
DUD322	adapter 1 for MK3	1
ATCS2010	adapter 2 for sleeve	1
DUF13	tightening range of chuck mandrel 5-20 mm	1
ATCS007	sleeves for RTR structural reinforcement system Ø16 mm	1
ATCS008	sleeves for RTR structural reinforcement system Ø20 mm	1





TECHNICAL DATA

Properties	values
Rated power consumption	2000 W
Drilling ∅ on:	
- solid drill bit for steel	up to 32 mm up to 1.26 in
- solid drill bit for woodt	up to 130 mm up to 5.12 in
- polypropylene with LS hole cutter	up to 600 mm up to 23.62 in
Rpm under load in 1st, 2nd, 3rd and 4th speed	120/210/380/650 U/min
Machine weight	8.6 kg 18.96 lbs
Collar diameter Ø	70 mm <i>2 3/4</i> "
Drill chuck connection	conical MK 3

COMPLEMENTARY PRODUCTS - ACCESSORIES

FRICTION

- Tightening torque 200 Nm | 147.5 ft-lbs
- Square connection 1/2"

CODE	pcs
DUVSKU	1



SCREW HANDLE

• High security

CODE	pcs
DUD38SH	1



ADAPTER 1

• For MK3

CODE	pcs
DUD322	1



ADAPTER 2

• For sleeve

CODE	pcs
ATCS2010	1



SLEEVES

• For WB structural reinforcement system

CODE	Ø [mm]	Ø [in]	pcs
ATCS007	16	0.63	1
ATCS008	20	0.79	1



MANDREL

• Adapter 1 (DUD322) is required for connection to the D 38 RLE drill

CODE	pcs
DUF13	1



RTR

STRUCTURAL REINFORCEMENT SYSTEM

CODE	d ₁	L	d_{hole}	d_1	L	d_{hole}	pcs
	[mm]	[mm]	[mm]	[in]	[in]	[in]	
RTR162200	16	2200	13	0.63	86.6	0.52	10
RTR202200	20	2200	16	0.79	86.6	0.63	5



For more information, see the "TIMBER SCREWS AND DECK FASTENING" catalogue, available in the "Catalogues" section of the website www.rothoblaas.com.