


TEMPORARY RAILING BARRIERS

EDGE TEMP 1

TEMPORARY RAILING
ROOF SIDE



CODES AND DIMENSIONS*

CODE	standard	material	max. slope of use	max. spacing between supports		minimum thickness of fixture [mm] [in]	substructure	weight [kg]	pcs
				[mm]	[in]				
EDGETEMP1	EN 13374 Class A	zinc-plated steel	used as a lateral protection support, with a maximum slope of 10° from horizontal	1400	55 1/8	from 80 to 192 from 3 1/8 to 7 9/16	 timber beam	8,80	1


* The values indicated are derived from experimental tests carried out under the supervision of third party organisations according to the referenced standard. For a calculation report with minimum distances, according to the referenced normative requirements, the substructure must be verified by a qualified engineer before installation.

EDGE TEMP 2

TEMPORARY RAILING
ROOF FRONT



CODES AND DIMENSIONS*

CODE	standard	material	max. slope of use	max. spacing between supports		minimum thickness of fixture [mm] [in]	substructure	weight [kg]	pcs
				[mm]	[in]				
EDGETEMP2	EN 13374 Class B	zinc-plated steel	maximum roof slope 30°	1400	55 1/8	from 80 to 200 from 3 1/8 to 8	 timber beam	9,00	1

* The values indicated are derived from experimental tests carried out under the supervision of third party organisations according to the referenced standard. For a calculation report with minimum distances, according to the referenced normative requirements, the substructure must be verified by a qualified engineer before installation.