

# FALL PROTECTION AND POSITIONING

## DOUBLE SICUROPE

CE

### DOUBLE ARM ROPE WITH ENERGY ABSORBER

- Complete with steel carabiner with screw ring nut and two aluminium connectors with double safety catch
- Energy absorber with activation indicator
- Protective fabric holder for energy absorber with Velcro closure

#### CODES AND CHARACTERISTICS

CODE	standard	L		weight [g]	pcs
		[m]	[ft]		
DSIC15	CE - EN 355	1,5	4' 11"	890	1
DSIC2	CE - EN 355	2	6' 6 3/4"	930	1



## SCAFFOLD DUO

CE

### DOUBLE ARM ROPE WITH ENERGY ABSORBER

- Complete with steel carabiner with screw ring nut and two aluminium large aperture (56 mm) connectors with double safety catch included
- Energy absorber with activation indicator
- Protective fabric holder for energy absorber with Velcro closure

#### CODES AND CHARACTERISTICS

CODE	standard	L		weight [g]	pcs
		[m]	[ft]		
SCA15	CE - EN 355	1,5	4' 11"	1540	1



## SICUROPE

CE

### SINGLE ARM ROPE WITH ENERGY ABSORBER

- Complete with steel carabiners with screw ring nut
- Protective fabric holder for energy absorber with Velcro closure
- Energy absorber with activation indicator

#### CODES AND CHARACTERISTICS

CODE	standard	L		weight [g]	pcs
		[m]	[ft]		
SIC15	CE - EN 355	1,5	4' 11"	715	1
SIC2	CE - EN 355	2	6' 6 3/4"	755	1

