

XXL



CONNECTOR WITH HIGH BREAKING LOAD

- Connector with wide opening and high breaking load. The "D" shape prevents the connector from rotating and allows the load to be distributed along the major axis

CODES AND DIMENSIONS

CODE	standard	weight [g]	<> [kN]	∧ [kN]	pcs
XXLSTE	CE - EN 362/M	260	50	15	1
XXLALU	CE - EN 362/B - EN 12275/B	95	30	15	1
XXLANS	CE - EN 362/M - ANSI Z359.12	273	50	20	1
XXLA4	CE - EN 362/B	250	35	7	1
XXLRISE	CE - EN 362/B	260	50	15	1



XXLSTE

XXLALU

XXLANS



XXLA4

XXLRISE

HELICON



HELICAL CONNECTOR WITH TWISTED BODY

- Special helical connector with twisted steel body
- Allows any device (descenders, ascenders, fall arrest devices, etc.) to be rotated by 90°, optimising its operating condition
- Auto Block locking ring (3 movements) available in both CE and ANSI versions

CODES AND DIMENSIONS

CODE	standard	weight [g]	<> [kN]	∧ [kN]	🔒 [kN]	pcs
HELICON	CE - EN 362/M	215	40	15	13	1
HELICONANSI	CE-EN 362/M ANSI Z359.12	230	40	15	13	1
HELICONALU	CE - EN 362/B EN 12275/B	80	24	8	7	1



HELICON



HELICONANSI



HELICONALU