

I PATROL + SOLID

LIFELINE ON RIGID SUPPORT FOR ROPE ACCESS WORK

DESIGNED FOR ROPE ACCESS WORK

The high-rigidity and high-strength support, combined with the jaw-plate anchor system, enables comfortable and safe rope access work.

LIGHT

The aluminium alloy of the support facilitates handling and installation thanks to the lightweight components.


ADAPTABLE

Support height between 400 and 1000 mm to adapt to different roofing thicknesses.

EN 795:2012 C	CEN/TS 18415:2013	UNI 11578:2015 C	AS/NZS 1891.4:2009	AS/NZS 1891.2:2001	BS 8610:2017 A3/A5	AS/NZS 5532:2013
---------------------	----------------------	------------------------	-----------------------	-----------------------	--------------------------	---------------------

ANSI* Z359.18 -2017 A

*The system has been developed and tested in accordance with the static, dynamic and residual strength requirements outlined in the relative ANSI standard.



**MAXIMUM NUMBER
OF USERS**



LOAD DIRECTION



**TYPES OF
APPLICATION**



SOFTWARE



BIM




VIDEO



MANUALS




PATROL LIFELINE COMPONENTS



TECHNICAL DATA**

substructure	minimum thickness	fasteners
CLT	160 mm	VGS (EVO) Ø13 HUS12
C20/25	-	INA Ø16 8.8
S235	15 mm	bolt or rod M12 10.9

substructure	minimum thickness	fasteners
C20/25	140 mm	AB1 Ø12
		SKR (EVO) Ø12
		INA Ø12 8.8 VIN-FIX



users	no.				
work method		fall protection/restraint		suspension	
minimum span	x _{min} [m]	2		-	-
maximum span	x _{max} [m]	15		-	-
maximum deflection	y _{max} [m]	3,35		-	-

**The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a correct calculation report with minimum distances according to the standard requirements, the substructure must be checked by a qualified engineer before installation.

SOLID | CODES AND DIMENSIONS

CODE	description	material	d ₁ [mm] [in]	B [mm] [in]	L [mm] [in]	H [mm] [in]	pcs	
SOLID400	rigid support for rope access work	EN AW-6082-T6	120 4.73	220,5 8 11/16	- -	400 15 3/4	1	
SOLID600			120 4.73	220,5 8 11/16	- -	600 23 5/8	1	
SOLID800			120 4.73	220,5 8 11/16	- -	800 31 1/2	1	
SOLID1000			120 4.73	220,5 8 11/16	- -	1000 39 3/8	1	
SOLIDRIG	jaw system for rope access work	EN AW-6082-T6	300 11.82	- -	- -	- -	1	
SOLIDPLATE	bottom plate for timber and concrete	EN AW-6082-T6	- -	550 21 5/8	595 23 7/16	- -	1	
SOLIDPLATEHD	bottom plate for timber and concrete for heavy-duty applications	EN AW-6082-T6	- -	650 25 9/16	695 27 3/8	- -	1	
SOLIDPLATEHC	bottom plate and counterplate for aerated concrete	EN AW-6082-T6	- -	650 25 9/16	545 21 7/16	- -	1	