

BORMAX GUIDE

PRECISION CUTTER FOR TIMBER

CODES AND DIMENSIONS

CODE	Ø cutter		Ø inside hole for centring		Ø shank		TL		EL		pcs
	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	
F1614020	20	0.79	8	5/16	13	1/2	140	5 1/2	90	3 1/2	1
F1614025	25	0.98	8	5/16	13	1/2	140	5 1/2	90	3 1/2	1
F1614030	30	1.18	8	5/16	13	1/2	140	5 1/2	90	3 1/2	1
F1614035	35	1.38	8	5/16	13	1/2	145	5 11/16	95	3 3/4	1
F1614040	40	1.58	10	3/8	13	1/2	145	5 11/16	95	3 3/4	1
F1614045	45	1.77	10	3/8	13	1/2	150	6	100	4	1
F1614050	50	1.97	10	3/8	13	1/2	150	6	100	4	1
F1614055	55	2.17	10	3/8	13	1/2	150	6	100	4	1
F1614060	60	2.36	10	3/8	13	1/2	150	6	100	4	1
F1614065	65	2.56	10	3/8	13	1/2	155	6 1/8	105	4 1/8	1
F1614070	70	2.76	10	3/8	13	1/2	155	6 1/8	105	4 1/8	1
F1614075	75	2.95	10	3/8	13	1/2	155	6 1/8	105	4 1/8	1
F1614080	80	3.15	10	3/8	13	1/2	155	6 1/8	105	4 1/8	1
F1614100	100	3.94	10	3/8	16	5/8	160	6 1/4	110	4 3/8	1
F1614110	110	4.33	10	3/8	16	5/8	160	6 1/4	110	4 3/8	1
F1614120	120	4.72	10	3/8	16	5/8	160	6 1/4	110	4 3/8	1

Including a centering drill bit and a hexagonal wrench.



TL total length

EL effective length



DRILL BIT FOR PRE-DRILLING

CODE	Ø shank	for cutters with Ø	TL	EL	pcs
	[mm] [in]	[mm] [in]	[mm] [in]	[mm] [in]	
F1614208	8 5/16	20 - 35 0.79 - 1.38	75 3	50 2	1
F1614210	10 3/8	40 - 120 1.58 - 4.72	75 3	50 2	1



CENTERING DRILL BIT

CODE	Ø	Ø shank	for cutters with Ø	pcs
	[mm] [in]	[mm] [in]	[mm] [in]	
F1619208	3,15 0.12	8 5/16	20 - 35 0.79 - 1.38	1
F1619210	4,0 0.16	10 3/8	40 - 120 1.58 - 4.72	1



GUIDING PIN

CODE	Ø	Ø shank	for cutters with Ø	TL	EL	pcs
	[mm] [in]	[mm]	[mm] [in]	[mm] [in]	[mm] [in]	
F1619008	8 0.32	8 5/16	20 - 35 0.79 - 1.38	75 3	50 2	1
F1619110	10 0.39		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619112	12 0.47		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619114	14 0.55		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619116	16 0.63		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619118	18 0.71		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619120	20 0.79		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619012	12 0.47	10 3/8	40 - 120 1.58 - 4.72	75 3	50 2	1
F1619014	14 0.55		40 - 120 1.58 - 4.72	75 3	50 2	1
F1619016	16 0.63		40 - 120 1.58 - 4.72	75 3	50 2	1
F1619018	18 0.71		40 - 120 1.58 - 4.72	75 3	50 2	1
F1619020	20 0.79		40 - 120 1.58 - 4.72	75 3	50 2	1



DEPTH STOP

CODE	for cutters with Ø	Ø internal	pcs
	[mm] [in]	[mm] [in]	
F1619100	40 - 90 0.79 - 3.54	95 3 3/4	1

